

- DMH A13 – offline Cascade CS-6 for the Q of 4.57 cfs – Standard Oil Storage Capacity of the CS-6 is 475 gallons
- DMH B10 – Online Cascade CS-4 for the Q of 1.9 cfs – Standard Oil Storage Capacity of the CS-4 is 141 gallons
- DMH C10 – Online Cascade CS-5 for the Q of 2.86 cfs - Standard Oil Storage Capacity of the CS-5 is 269 gallons
- DMH E19 – Online Cascade CS-6 for the Q of 3.72 cfs – Standard Oil Storage Capacity of the CS-6 is 475 gallons
- DMH J3 – Online CDS 1515-3 for the Q of 0.28 cfs - Standard Oil Storage Capacity of the CDS 1515-3 is 34 gallons (Stormceptor model STC 450 with treatment Capacity to 0.40 cfs can be considered and has Oil Storage Capacity of 86 gallons.)

Cascade			
Model	Flow Rate (cfs)	Sediment Capacity (CF)	Oil Storage Capacity / gal
CS-4	2.00	19	141
CS-5	3.50	29	269
CS-6	5.60	42	475
CS-8	12.00	75	1128
CS-10	18.00	118	2203

CDS			
Model	Flow Rate (cfs)	Sediment Capacity (CF)	Oil Storage Capacity / gal
1515-3	1.00	14	34

Stormceptor STC			
Model	Flow Rate (cfs)	Sediment Capacity (CF)	Oil Storage Capacity / gal
STC 450i	0.40	46	86

Jim Lyons
Stormwater Consultant

Contech Engineered Solutions LLC